

Conventional Manual Call Point

CCP-SAVWIRE



Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Designed for use on "Savwire" (two-wire) systems

Description

The CCP-SAVWIRE is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals. The unit has been specifically designed for use on "Savwire" (two-wire) systems.

The unit can support either a 'Frangible Glass' element or a 'Non Frangible Plastic' element.

Specification		
Ordering Code	CCP-SAVWIRE	
Nominal operating resistance	470 Ω	
Maximum contact resistance (R)	200 Ω	
Ingress Protection Rating	IP24D	
Operating Temperature Range	-10 °C to + 55 °C	
Storage Temperature Range	-10 °C to + 55 °C	
Maximum Humidity	95%RH - Non condensing (at 40 °C)	
Colour / Case Material	Red / ABS	
Weight (g) / Dimensions (mm)	(Flush Mount) 110 / W89 x H93 x D27.5	
	(Surface Mount with Back Box) 160 / W89 x H93 x D59.5	
Accessories	Frangible Element	KAC/G/HE
	Non-Frangible Element	KAC/EWS/HE